



"WE CAN AGUASEAL THAT"

AGUASEAL WATERPROOFING SYSTEMS

STREETSEAL

STREETSEAL



WHAT IS STREETSEAL?

StreetSeal is an environmentally friendly, water-based, high quality acrylic polymer sealant that permeates into the asphalt matrix. The product dries to form an extremely tight, efficient seal that minimizes any water penetration into the substrate.

StreetSeal completely rejuvenates the asphalt or block-pave system, leaving a newly laid appearance. In doing so, it covers minor cracks and imperfections.

Unlike competitor products, StreetSeal does not incorporate any bulking fillers. These fillers minimize absorption into the actual asphalt or pave, which prevents deep rejuvenation of the surface.



APPLICATION INSTRUCTIONS

SURFACE PREPARATION:

Ensure the surface is clean and dry.

RECOMMENDED APPLICATION:

Spray, roller, or brush.

COVERAGE: (Dependent on surface) 140 sq. ft. - 160 sq. ft. per coat, per gallon. It is suggested that a small trial be conducted on the particular project substrate to provide an accurate product requirement assessment. Two coats may be required in areas of increased wear.

DRY FILM THICKNESS:

(Substrate Dependent) 20 - 40 mils / 0.5mm - 1.0mm. On most surfaces StreetSeal will penetrate the substrate, leaving little or no surface film.

APPLICATION TEMPERATURE:

41F - 100F / 5C - 40C

DRYING TIME: (Touch dry) at 68F at 55% relative humidity = 1 hour.

FREEZE POINT: 32F / 0C.



TECHNICAL DATA

STREETSEAL

Dry solids by volume	49%
Solids by weight	43%
Density	8.76 lbs per US gallon 1.05 kg per liter
Shelf Life	24 months if stored out of direct sunlight between 40F (4C) to 95F (35C)
Surface Finish	Semi-gloss
Clean Up	Water
Colors	Black and Clear (clear is mainly for rejuvenating previously colored areas and block paving)

SAFETY & HANDLING

For specific information regarding safe handling of StreetSeal please refer to the Safety Data Sheet.

AGUASEAL WATERPROOFING SYSTEMS USA, LLC

CHARLESTON, SC | WWW.AGUASEAL.NET

INFO@AGUASEAL.NET | 843 614 9663